





## T5 LED Batten Lighting

| Power Consumption                                                                                                                                                       | Dimension                                                                                             | Part No.                       | CCT                        | LUX (lm)     | No. of Wiring Holes | Traditional Light Power Wattage Replacement |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|--------------------------------|----------------------------|--------------|---------------------|---------------------------------------------|
| <br>     | <br>295*22*34(mm)    | SYT5S05-CW-40<br>SYT5S05-WW-40 | 6500K<br>3000K             | 450<br>450   | dual ports          | T8 glass tubing 10W<br>T5 glass tubing 8W   |
| <br>    | <br>560*22*34(mm)    | SYT5S10-CW-40<br>SYT5S10-WW-40 | 6500K<br>3000K             | 800<br>800   | dual ports          | T8 glass tubing 20W<br>T5 glass tubing 14W  |
| <br> | <br>860*22*34(mm)  | SYT5S15-CW-40<br>SYT5S15-WW-40 | 6500K<br>3000K             | 1200<br>1200 | dual ports          | T8 glass tubing 20W<br>T5 glass tubing 14W  |
| <br> | <br>1160*22*34(mm) | SYT5S20-CW-40<br>SYT5S20-WW-40 | F6500K<br>F4000K<br>F3000K | 1600<br>1600 | dual ports          | T8 glass tubing 40W<br>T5 glass tubing 28W  |